

THIS CAT WAS MADE TO GET INTO TREES

In fact, this "cat" will claw right through limbs for a clean, precise cut every time. The Timber Cat® is like no other limb cutter on the market. This durable machine features a unique cut that allows debris to fall directly to the ground instead of being thrown. So cut those trees down to size, you've got the Timber Cat on your side!

Timber Cat[®]
Sickle Bar Limb Cutter

ALAMO[®]
INDUSTRIAL

Timber Cat[®] Tree Limb Cutter

BUILT SHARPER[™]

Timber Cat® Tree Limb Cutter

The Timber Cat® Sickle Bar is ideal for anyone with limb cutting jobs in heavily populated areas such as subdivisions, school grounds, playgrounds, and industrial parks where a manicured appearance is essential. The fear of cut material being thrown from the cutting head, endangering pedestrians as well as nearby buildings and windows, is virtually eliminated. As the limbs are cut, they simply fall straight to the ground for disposal, making clean-up easier and less time consuming for the operator. Safety, efficiency, and appearance is what the Alamo Industrial® Timber Cat Sickle Bar is all about.

Power

The head is hydraulically powered with use of an inversion valve and 3" bore cylinder to control the reciprocating motion of the cutting surfaces. Operating at 1500 PSI, there is 2,650 pounds of force available to shear material. The mechanical over hydraulic valve has an automatic reverse, which accommodates the need to back out of a cut should that be necessary.

Easy Maintenance

As greasing before each use ensures efficient operation of the reciprocating motion, two easily accessible grease points on the top cover allow for convenient maintenance of the cutter bar blades.

Blades

The heavy-duty cutter bar is made of two 5/8" thick blades constructed from T-1 alloy steel. Cycling at 50 times per minute, it is capable of easily slicing through up to 4" thick tree limbs. A polyethylene bearing surface is featured between the reciprocating cutting bar and the front shield to promote longer life.

The quick cutting action allows the machine to leave behind a smooth and clean cut appearance.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2003 Alamo Group Inc. Alamo Industrial and Timber Cat are registered trademarks of Alamo Group Inc.



Durable Mount

The Timber Cat mounts to all Alamo Industrial® Boom Mowers including the A-Boom, Versa® Boom, Machete®, and Rear Mount Boom which are available in ranges from 17' up to 28'. When used in conjunction with the Quick Hitch® quick attach system, the head can be taken off and switched with another cutting head in minutes!

A heavy-duty hitchpost design provides a strong connection to the boom for increased durability. A formed, 3/16" thick, front cover provides complete protection of the reciprocating blade controls.



Quick Hitch® quick attach system.



Additional Specifications

Cutting Widths	60" (5')	84" (7')
Approximate Weight	440 lbs.	520 lbs.

Tractor Requirements: Minimum 5,000 lb. range and 45 HP to accommodate both the boom and the head. This information is approximate for the smallest boom package offered. Minimum tractor weights and horsepower ratings are subject to change in accordance with boom selection and if other heads will be used.

Warranty: One year limited parts and labor. Non-governmental users are subject to modified policy. Only genuine Alamo Industrial parts should be used for warranty replacement.



BUILT SHARPER™

1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com