Maverick 2

Mid-Mount Boom Mower









Built for Strength
Built to resemble the strength & durability of a backhoe arm, the Maverick 2 has strength where needed.

Mow Inches from the Tire
180° swing path allows the operator to mow within 6" of the tire.

Maximum Reach of 30'
Four bar linkage allows the cutting head to be maneuvered at greater angles making it easier to cut in hard-to-reach areas.

Piston pump boom with a turret-style mount giving it a 180° front to back hydraulic swing.

Boom Reach Options
24', 28' and 30'
*with 60" Rotary Head

Other Available Attachments

Battle Axe	SD Rotary Head
Ditcher	SRD50 Mulcher
Flail Axe®	Buzz Bar®
HD Grass Flail	Timber Cat

Tractor Minimums
10,500lbs & 90PTO HP
90" wheelbase
18" ground clearance
CAB

ALAMO INDUSTRIAL®

Alamo-Industrial.com | sales@alamo-industrial.com

Sourcewell - Contract No. 070821-AGI
Canoe Canada - Contract No. 070821-AGI
GSA - Contract No. GS-30F-0008S
Buy Board - Contract No. 611-20

©2022 Alamo Industrial or its affiliates. 2022 Alamo Group Texas All rights reserved. This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: One year limited parts and labor. Non-governmental users are subject to modified policy. Only genuine Alamo Industrial parts should be used for warranty replacement.



ALAMO INDUSTRIAL Maverick 2