Versa® Rotary

Mid-Mount Rotary







Hydraulics

The Versa® Rotary Mower has a self-contained hydraulic system with a large under fender oil reservoir that provides adequate cooling for the 55 gallon capacity system. Steel gear type pump rated at 74 HP and 51 GPM at 2,400 RPM with a maximum operating pressure of 3,000 PSI.

Mower Lift Assembly

Capable of mowing from 90-degrees up to 45-degrees down, raising 17" vertically and lowering to 6" below grade* and consists of a 3 1/2" Bore Lift & Tilt Cylinder.
*Depends on Tractor Configuration

Versa® controls have "float" positions that allow the rotary head to follow terrain contours without operator control.

Cutting Swath
60" or 72"

Cutting Capacity
2"

30° break-away option for 60" rotary

Front & Rear Double Chain Guards

Full-length Replaceable Skid Shoes

Available with a Blade-Bar or a Blade-Pan

ALAMO INDUSTRIAL®

Alamo-Industrial.com | sales@alamo-industrial.com

Sourcewell - Contract No. 070821-AGI
Canoe Canada - Contract No. 070821-AGI
GSA - Contract No. GS-30F-0008S
Buy Board - Contract No. 611-20

©2022 Alamo Industrial or its affiliates. 2022 Alamo Group (TX) All rights reserved. This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: One year limited parts and labor. Non-governmental users are subject to modified policy. Only genuine Alamo Industrial parts should be used for warranty replacement.